

Wise Machinery Co., Ltd.

Crown Grinding (RG Series) Attachments for Lathe – Specifications

The Crown Height Range of All the Models Below Is From 0.01 mm to 8.00 mm.

ITEM	MODEL	Type	Main Motor	Wheel Size	Spindle Speed
1	RG30F-10 x 2300 rpm	Front	3.0 HP	10 inch	2300 rpm
2	RG30R-10 x 2300 rpm	Rear	3.0 HP	10 inch	2300 rpm
3	RG50F-12 x 1800 rpm	Front	5.0 HP	12 inch	1800 rpm
4	RG50R-12 x 1800 rpm	Rear	5.0 HP	12 inch	1800 rpm
5	RG75F-10 x 6700 rpm	Front	7.5 HP	10 inch	6700 rpm
6	RG75R-10 x 6700 rpm	Rear	7.5 HP	10 inch	6700 rpm
7	RGH75F-16 x 1400 rpm	Front	7.5 HP	16 inch	1400 rpm
8	RG100F-10 x 6700 rpm	Front	10.0 HP	10 inch	6700 rpm
9	RG100R-10 x 6700 rpm	Rear	10.0 HP	10 inch	6700 rpm
10	RGH100F-16 x 1400 rpm	Front	10.0 HP	16 inch	1400 rpm
11	RGH150F-20 x 1000 rpm	Front	15.0 HP	20 inch	1000 rpm

Attention: Item 5, 6, 8, and 9 are high speed models which can only be equipped with Rubberhog wheel.

Website: www.wiseliu.com

Email: wiseliu@ms1.hinet.net

Tel: 886-4-25276666

Fax: 886-4-25201499

F-Type (Most Commonly Used)



R-Type



Functions of our RG-Series: (Two Different Combinations for You to Choose)

- (1) Convex / Taper End / Cylindrical Grinding
- (2) Convex / Concave / Cylindrical Grinding

Our grinding attachments can be mounted onto any size of existing lathes without modification.

They are perfectly suitable for Rubber (PU, Plastic, and Fiber) Rollers manufacturers, users, and workshops.

We believe it is an economic & efficient way to grind your rollers. Thank you.

Website: www.wiseliu.com

Email: wiseliu@ms1.hinet.net

Tel: 886-4-25276666

Fax: 886-4-25201499